




Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.













3 RECOMMENDED PATTERN



APPLICATION DRAWING



NOTES 1 : WHEN THIS CONNECTOR MATES WITH DF13-9S-1.25C, THE MATING HEIGHT IS 5.8mm.
2 : LEAD CO-PLANARITY INCLUDING REINFORCED METAL FITTINGS SHALL BE WITHIN 0.1mm.
3 : RECOMMENDED THICKNESS OF CREAM SOLDER PASTE:0.15mm ~ 0.2mm
OPEN AREA RATIO:100%

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	BRASS	SURFACE:TIN PLATED 1μm min.	5	POLYESTER	COVER TAPE, CLEAR
1	POLYAMIDE	UL94V-0, BEIGE	4	PS	EMBOSSED CARRIER TAPE, CLEAR
			3	PHOSPHOR BRONZE	SURFACE:TIN PLATED 1μm min.

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1					

HIROSE ELECTRIC CO., LTD.

APPROVED	TS. SAKATA	08.09.01
CHECKED	TS. KUMAZAWA	08.08.29
DESIGNED	SN. KOBAYASHI	08.08.26
DRAWN	SN. KOBAYASHI	08.08.26

DRAWING NO.	EDC3-083417-01
PART NO.	DF13C-9P-1.25V(21)
CODE NO.	CL536-0408-1-21


△ 1/2

FORM HC0011-5-7

PRS DRAWING FOR REFERENCE


© 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

A PORTION (FREE)




DIRECTION OF UNREELING


B-B



STYLE AND DIMENSION OF REEL (FREE)



C-C



6 DETAIL OF PART No. LABEL

- SUPPLIER
- QUANTITY
- PART No.
- CODE No.
- DATE OF MANUFACTURED

生産月日	年　月　日
図番	CL536-0408-1-21
品番	DF13C-9P-1.25V(21)
納入数量	1000ko
納入者	ヒロセ電機(株)

NOTES 4 : 1REEL:1000 CONNECTORS.
5 : AT THE BEGINNING OF THE REEL, 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.
6 : DETAIL OF PART No. LABEL IS WRITTEN IN JAPANESE.

HRS DRAWING FOR REFERENCE

DRAWING NO.	EDC3-083417-01
PART NO.	DF13C-9P-1.25V(21)
CODE NO.	CL536-0408-1-21

△ 2/2