

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-35°C TO + 85°C (NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO + 60°C (NOTE 2)	
	VOLTAGE	150V AC	APPLICABLE CONNECTOR	DF13/DF13A-40DP-1.25V (55)	
	CURRENT	1A		DF13/DF13A-40DP-1.25V (56)	
SPECIFICATIONS					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING		CONFIRMED VISUALLY.		X	X
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE		100m A (DC OR 1000 Hz).	30mΩ MAX.	X	—
INSULATION RESISTANCE		100V DC.	500MΩ MIN.	X	—
VOLTAGE PROOF		500V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION		50TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 30mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	—
ENVIRONMENTAL CHARACTERISTICS					
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55→ 5 TO 35→+85→ 5 TO 35 °C TIME 30→ 2 TO 3 → 30→ 2 TO 3 min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30mΩ MAX. ② INSULATION RESISTANCE: 500MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 30mΩ MAX. ② INSULATION RESISTANCE: 500MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
CORROSIN,SALT MIST		EXPOSED IN 5% SALT WATER SPRAY FOR 48h.	NO HEAVY CORROSION.	X	—
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96h. (TEST STANDARD: JEIDA-39)	NO HEAVY CORROSION.	X	—
RESISTANCE TO SOLDERING HEAT		SOLDER TEMPERATURE, 260±5°C, FOR IMMERSION, DURATION, 5S.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X	—
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, 230±10°C FOR INSERTION DURATION, 3 SECONDS.	SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.	X	—
REMARKS					
NOTE 1:INCLUDING THE TEMPERATURE RISE BY CURRENT.					
NOTE2:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD AFTER PCBBOARD , OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERM STORAGE DURING TRANSPORTATION.					
Unless otherwise specifid , refer to JIS C 5402.					
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△					
			APPROVED	TY.OMA	06.02.02
			CHECKED	HK.UMEHARA	06.02.02
			DESIGNED	TS.KUMAZAWA	06.01.31
			DRAWN	AK.MIURA	06.01.25
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-160787-02	
HRS	SPECIFICATION SHEET		PART NO.	DF13-40DS-1.25DSA (55)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL536-0635-3-55	△ 1/1