Jan.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .









PART NO.	CODE NO.	NUMBER OF CONTACTS	A	B	C
DF1- 2P-2.5DSA(05)	541-0001-0-05	2	7.5	3.8	2.5
DF1- 3P-2.5DSA(05)	541-0002-2-05	3	10.0	6.3	5.0
DF1- 4P-2.5DSA(05)	541-0003-5-05	4	12.5	8.8	7.5
DF1- 5P-2.5DSA(05)	541-0004-8-05	5	15.0	11.3	10.0
DF1- 6P-2.5DSA(05)	541-0005-0-05	6	17.5	13.8	12.5
DF1- 7P-2.5DSA(05)	541-0006-3-05	7	20.0	16.3	15.0
DF1- 8P-2.5DSA(05)	541-0007-6-05	8	22.5	18.8	17.5
DF1- 9P-2.5DSA(05)	541-0008-9-05	9	25.0	21.3	20.0
DF1-10P-2.5DSA(05)	541-0009-1-05	10	27.5	23.8	22.5
DF1-11P-2.5DSA(05)	541-0010-0-05	11	30.0	26.3	25.0
DF1-12P-2.5DSA(05)	541-0011-3-05	12	32.5	28.8	27.5
DF1-13P-2.5DSA(05)	541-0012-6-05	13	35.0	31.3	30.0
DF1-14P-2.5DSA(05)	541-0013-9-05	14	37.5	33.8	32.5
DF1-15P-2.5DSA(05)	541-0014-1-05	15	40.0	36.3	35.0
DF1-16P-2.5DSA(05)	541-0015-4-05	16	42.5	38.8	37.5
DF1-18P-2.5DSA(05)	541-0017-0-05	18	47.5	43.8	42.5
DF1-20P-2.5DSA(05)	541-0019-5-05	20	52.5	48.8	47.5

NOTES 1: 2 POSITION TO BE SLOTTED AT CENTER FOR ONE LOCATION OTHER POSITIONS TO BE 2 LOCATIONS AS SHOWN IN FIGURE.
2: IN THE CASE OF 2 TO 6 CONTACTS, THERE IS NO MIS-INSERTION DEPRESSION.
FOR 7 TO 12 CONTACTS, ONE MIS-INSERTION DEPROSSION.
FOR OTHERS, 2 MIS-INSERTION DEPRESSION AS SHOWN IN A FIGURE.

HRS DRAWING FOR REFERENCE

NO.	MATERIAL	FINISH, REMARKS
1	BRASS	SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL 0.5μm min
2	POLYAMIDE	PALE BROWN,UL94V-0

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	M.Nakamoto '04.04.16	H.Umehara 04.04.16	T.Ota 04.04.16	T.Ota 04.04.16	. .

SCALE	DRAWING NO.	PART NO.
5 : 1	EDC3-162342-10	DF1-*P-2.5DSA(05)
UNITS: mm	HIROSE ELECTRIC CO., LTD	CODE NO. CL541- 1/1

TO

FORM NO.229