

Dec.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△					
△					△					
APPLICABLE STANDARD										
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10 °C To + 60 °C				
	VOLTAGE				APPLICABLE CONNECTORS					
	CURRENT				OPERATING HUMIDITY RANGE	UL1007, AWG24				
SPECIFICATIONS										
ITEM	TEST METHOD				REQUIREMENTS				QT	AT
CONSTRUCTION										
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.				X	X
MARKING		CONFIRMED VISUALLY.							X	X
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT					Y.NAGASHIMA	<i>Y. Inoue</i>	<i>Miyazaki</i>	<i>K. Katayama</i>		
Unless otherwise specified, refer to MIL-STD-1344.					'00.11.10	'00. 11. 10	'00. 11. 13	'00.11.14		
Note QT: Qualification Test AT: Assurance Test X:Applicable Test										
HRS HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET			PART NO.		
					DF 1 - * A 1 . 3 3					
CODE NO.(OLD)			DRAWING NO.			PEART NO			1	
CL			ELC4-162341			CL 5 4 1			1	

TO

