

Feb. 1. 2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
APPLICABLE STANDARD											
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10 °C To + 60 °C					
	VOLTAGE				APPLICABLE CONNECTORS						
	CURRENT				OPERATING HUMIDITY RANGE	UL1007, AWG24					
SPECIFICATIONS											
ITEM	TEST METHOD				REQUIREMENTS				QT	AT	
CONSTRUCTION											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.				×	×	
MARKING		CONFIRMED VISUALLY.							×	×	
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT					Y.NAGASHIMA	<i>Y. Inoue</i>	<i>Miyazaki</i>	<i>K. Katayama</i>			
Unless otherwise specified, refer to MIL-STD-1344.					'00.11.10	'00. 11. 10	'00. 11. 13	'00.11.14			
Note QT: Qualification Test AT: Assurance Test ×:Applicable Test											
HRS HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET					PART NO.	
										DF 1 - * A 1 . 3 3	
CODE NO.(OLD)			DRAWING NO.			PEART NO				1	
CL			ELC4-162341			CL 5 4 1				1	

TO

