Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO +85 °C(NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C
	OPERATING HUMIDITY RANGE	UL1007, AWG26,28		

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△0					

REMARKS
NOTE1:INCLUDING THE TEMPERATURE RISING BY CURRENT.

Unless otherwise specified, refer to JIS C 5402.

APPROVED	TY.OMA	05.12.28
CHECKED	HK.UMEHARA	05.12.28
DESIGNED	NS.HIROSE	05.12.27
DRAWN	AK.MIURA	05.12.27

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-162340-01

HRS	SPECIFICATION SHEET	PART NO.	DF1-*A1.05	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL541 △0	1/1

FORM HD0011-2-1