Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.







HRS DRAWING FOR REFERENCE

CODE No.	PART No.	NUMBER OF CONTACT	A	B
541-0115-9-05	DF1- 2S-2.5R28(05)	2	8.0	2.5
541-0116-1-05	DF1- 3S-2.5R28(05)	3	10.5	5.0
541-0117-4-05	DF1- 4S-2.5R28(05)	4	13.0	7.5
541-0118-7-05	DF1- 5S-2.5R28(05)	5	15.5	10.0
541-0119-0-05	DF1- 6S-2.5R28(05)	6	18.0	12.5
541-0120-9-05	DF1- 7S-2.5R28(05)	7	20.5	15.0
541-0121-1-05	DF1- 8S-2.5R28(05)	8	23.0	17.5
541-0122-4-05	DF1- 9S-2.5R28(05)	9	25.5	20.0
541-0123-7-05	DF1-10S-2.5R28(05)	10	28.0	22.5
541-0124-0-05	DF1-11S-2.5R28(05)	11	30.5	25.0
541-0125-2-05	DF1-12S-2.5R28(05)	12	33.0	27.5
541-0126-5-05	DF1-13S-2.5R28(05)	13	35.5	30.0
541-0127-8-05	DF1-14S-2.5R28(05)	14	38.0	32.5
541-0128-0-05	DF1-15S-2.5R28(05)	15	40.5	35.0
541-0129-3-05	DF1-16S-2.5R28(05)	16	43.0	37.5
541-0133-0-05	DF1-20S-2.5R28(05)	20	53.0	47.5

NOTES 1 2 POSITION TO BE PROTRUSION AT CENTER FOR ONE LOCATION 3 TO 6 POSITIONS UNLOCATED OTHER POSITION TO BE AS SHOWN IN FIGURE.
2 COLOR OF Δ MARKING: RED.
3 APPLICABLE CABLE: UL 1007 AWG28.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
1	POLYAMIDE	PALE BROWN, UL94V-0	2	PHOSPHOR BRONZE	SURFACE PLATING:TIN PRATING 2μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	2	1	DIS-H-006064	MI. SAKIMURA	HK. UMEHARA	11. 08. 05

HIROSE ELECTRIC CO., LTD.

APPROVED	TY. OMA	05. 12. 22
CHECKED	HK. UMEHARA	05. 12. 21
DESIGNED	NS. HIROSE	05. 12. 20
DRAWN	AK. MIURA	05. 12. 19

DRAWING NO.	EDC3-162346-01
PART NO.	DF1-*S-2.5R28(05)
CODE NO.	CL541- 2 1/1