




Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.












Recommended pattern (5:1)



HRS DRAWING FOR REFERENCE

Part No.	Code No.	Contact No.	A	B	C
CL541-0225-7-01	DF1B- 2P-2.5DSA(01)	2	7.5	2.5	6.9
CL541-0226-0-01	DF1B- 3P-2.5DSA(01)	3	10.0	5.0	9.4
CL541-0227-2-01	DF1B- 4P-2.5DSA(01)	4	12.5	7.5	11.9
CL541-0228-5-01	DF1B- 5P-2.5DSA(01)	5	15.0	10.0	14.4
CL541-0229-8-01	DF1B- 6P-2.5DSA(01)	6	17.5	12.5	16.9
CL541-0230-7-01	DF1B- 7P-2.5DSA(01)	7	20.0	15.0	19.4
CL541-0231-0-01	DF1B- 8P-2.5DSA(01)	8	22.5	17.5	21.9
CL541-0232-2-01	DF1B- 9P-2.5DSA(01)	9	25.0	20.0	24.4
CL541-0233-5-01	DF1B-10P-2.5DSA(01)	10	27.5	22.5	26.9
CL541-0235-0-01	DF1B-12P-2.5DSA(01)	12	32.5	27.5	31.9
CL541-0237-6-01	DF1B-14P-2.5DSA(01)	14	37.5	32.5	36.9
CL541-0238-9-01	DF1B-15P-2.5DSA(01)	15	40.0	35.0	39.4
CL541-0239-1-01	DF1B-16P-2.5DSA(01)	16	42.5	37.5	41.9
CL541-0240-0-01	DF1B-18P-2.5DSA(01)	18	47.5	42.5	46.9
CL541-0241-3-01	DF1B-20P-2.5DSA(01)	20	52.5	47.5	51.9

Note 1 When the numbers of contacts is odd.
The stand-off shifts 1.25 rightward.
(Stand-off available from 4 positions up.)

2 2 positions and 3 positions headers have 1 polarizing slot at center.
To 6 positions from 4 positions have 2 polarizing slots.
Other positions have 3 polarizing slots as per drawing.

NO.	MATERIAL	FINISH , REMARKS
1	Polyamide	UL94V-0, Natural(White)
2	Brass	Surface : Gold plated 0.2μm min. Under plating : Nickel plated 1μm min.

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	1	DIS-H-00004686	SN. MIWA	SZ. ONO	20190306

HIROSE ELECTRIC CO., LTD.

APPROVED	TY. OMA	20060805
CHECKED	HK. UMEHARA	20060805
DESIGNED	AH. MIYAZAKI	20060805
DRAWN	AK. MIURA	20060805

DRAWING NO.	EDC-071798-01-03
PART NO.	DF1B-*P-2.5DSA(01)
CODE NO.	CL541-

1/1