



Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



NOTES 1 DIE CAVITY No.
2 NUMBER OF CONTACT.
3 AT CONTACT No. 1 SIDE.
4 ONE SQUARE HOLE IN LOW ROW MEANS ODD NUMBER SIDE AND TWO SQUARE HOLES
IN UPPER LOW EVEN NUMBER OF CONTACT No. RESPECTIVELY.

SUFFIX	WIRE	WIRE CONSTRUCTION	OUTER DIAMETER OF INSULATION
R26	UL1061 AWG26	7/0.16	0.95 TO 1.05



2	PHOSPHOR BRONZE	SURFACE:TIN PLATED 1#m min UNDER PLATING:NICKEL PLATED 0.5#m min		3	PHOSPHOR BRONZE	SURFACE:TIN PLATED 1#m min UNDER PLATING:NICKEL PLATED 0.5#m min			
1	POLYAMIDE	UL94V-0, BLACK							
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS			
UNITS mm		SCALE 5 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.		APPROVED :TS. SAKATA		08.10.20	DRAWING NO.		EDC3-084867-01		
		CHECKED :TS. KUMAZAWA		08.10.17	PART NO.		DF11-18DS-2R26(05)		
		DESIGNED :KT. ISHII		08.10.16	CODE NO.		CL543-0659-0-05		
		DRAWN :KT. ISHII		08.10.16					
							1/1		