Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE







C—C



CABLE JOINT DIAGRAM





NOTES 1 DIE CAVITY No.
2 NUMBER OF CONTACT.
3 AT CONTACT No.1 SIDE.
4 ONE SQUARE HOLE IN LOW ROW MEANS ODD NUMBER SIDE AND TWO SQUARER HOLES IN UPPER LOW EVEN NUMBER OF CONTACT No. RESPECTIVELY.

SUFFIX	WIRE	WIRE CONSTRUCTION	OUTER DIAMETER OF INSULATION
R26	UL1061 AWG26	7/0.16	0.95 TO 1.05

NO.	MATERIAL	FINISH , REMARKS
2	PHOSPHOR BRONZE	SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL PLATED 0.5μm min
1	POLYAMIDE	UL94V-0, BLACK

NO.	MATERIAL	FINISH , REMARKS
3	PHOSPHOR BRONZE	SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL PLATED 0.5μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△					

HIROSE ELECTRIC CO., LTD.

APPROVED	TS. SAKATA	08. 10. 20	DRAWING NO. EDC3-084869-01
CHECKED	TS. KUMAZAWA	08. 10. 17	PART NO. DF11-22DS-2R26(05)
DESIGNED	KT. ISHII	08. 10. 16	
DRAWN	KT. ISHII	08. 10. 16	CODE NO. CL543-0661-1-05 △ 1/1