

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .




RECOMMENDED LAND PATTERN DIMENSION OF PCB



CROSS CUT SECTION - SIGNAL (5 : 1)



CROSS CUT SECTION - GROUND (5 : 1)



HRS DRAWING FOR REFERENCE

NOTES 1 12 HATCHED ▨ PARTS:GROUND CIRCUIT.
2 2 HATCHED ▨ PARTS:GROUND CIRCUIT.
3 SMT LEAD-COPLANARITY:0.1 MAX.
4 THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
5 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

NO.	MATERIAL	FINISH, REMARKS
1	LCP	BEIGE UL94V-0
3 , 4	PHOSPHOR BRONZE	TIN-PLATING
2	PHOSPHOR BRONZE	CONTACT AREA : GOLD 0.1μm min. LEAD AREA : GOLD FLASH UNDER PLATING : NICKEL 1μm min.

TO
PCK

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	A.SUZUKAWA 06.06.02	H.Nakamura '06.06.05	H.Ozawa '06.06.05	H.Okawa '06.06.06	. .

SCALE	DRAWING NO.	PART NO.
4 : 1	EDC3-151978-25	FX10A-120S/12-SV(71)
UNITS: mm	HIROSE ELECTRIC CO., LTD	CODE NO. CL570-0203-0-71 1/1