

Note

- 1 Lead CO-Planarity is 0.1mm MAX.
- 2 This is packaged in tray. (60pcs/tray)
- 3 It shows the vacuum pickup area. Remove the mylar tape before mating connectors.
- 4 Blemish and hit mark can be occurred through out the manufacturing process which doesn't affect quality level.
- 5 The dimensions in parentheses are for references.
- 6 Please use the connectors within the specified PCB distance.

				6	POLYIMIDE	(TAPE FOR VACUUM PICKUP)	
				5	POLYSTYRENE	(TRAY)	
2	COPPER ALLOY	CONTACT AREA:GOLD 0.1 μ m		4	BRASS	TIN-PLATING 1 μ m	
		LEAD AREA:GOLD 0.03 μ m		3	COPPER ALLOY	CONTACT AREA:GOLD 0.1 μ m	
		UNDER PLATING:NICKEL 1.3 μ m				LEAD AREA:TIN-PLATING 1 μ m	
1	POLYAMIDE	BLACK UL94V-0				UNDER PLATING:NICKEL 1.3 μ m	
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS	

UNITS mm		SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
		2 : 1						
 HIROSE ELECTRIC CO., LTD.	APPROVED : HS. OKAWA		16. 01. 20	DRAWING NO.	EDC-358061-00-00			
	CHECKED : KN. SHIBUYA		16. 01. 20	PART NO.	FX23L-100P-0. 5SV12			
	DESIGNED : TS. 00NO		16. 01. 20	CODE NO.	CL573-2205-5-00			
	DRAWN : TS. 00NO		16. 01. 20					