


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	3	RE-F-09671	K.N	H.Y	04.04.08						. .
					. .						. .
					. .						. .



RECOMMENDED LAND PATTERN DIMENSION OF P.C.B. (MOUNTING SIDE)







DIMENSION TABLE OF CONNECTOR AND P.C.B. LAND PATTERN.

PART No.	CODE No.	6	7	A	B	C	D	E
FX8C- 60P-SV1(93)	CL578-0521-6-93	60	×	24.60	23.00	20.70	17.40	22.20
FX8C- 80P-SV1(93)	CL578-0523-1-93	80	×	30.60	29.00	26.70	23.40	28.20
FX8C-100P-SV1(93)	CL578-0525-7-93	100	–	36.60	35.00	32.70	29.40	34.20
FX8C-120P-SV1(93)	CL578-0526-0-93	120	–	42.60	41.00	38.70	35.40	40.20
FX8C-140P-SV1(93)	CL578-0527-2-93	140	–	48.60	47.00	44.70	41.40	46.20

NOTE 1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
2. EMBOSSED CARRIER TAPE PACKAGING SHALL BE APPLIED TO THIS PRODUCT.
SEE NEXT PAGE FOR DETAILS.
3. THIS PRODUCT HAS TAPE FOR VACUUM PICKUP.
SEE NEXT PAGE FOR DETAIL OF STICKING POSITION,ETC.
4. FOR MODIFICATION,ETC,PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
5. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
6 NUMBER OF CONTACTS.
7 EXISTENCE
×:PRODUCED, -:NO PRODUCED

△1

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
1	PPS	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min LEAD AREA:TIN-PLATING 1μm min UNDER PLATING:NICKEL 1μm min

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	S.SUZUKI 03.02.03	K.NAKAMURA 03.02.12	H.OKAWA 03.02.14	Y.YOSHIMURA 03.02.15	. .

TO
PCK

SCALE FREE
UNITS mm


DRAWING NO. EDC3-151087-23
PART NO. FX8C-**P-SV1(93)
HRS HIROSE ELECTRIC CO., LTD
CODE NO. CL578
1/2


FIRST DRAWING FOR REFERENCE

Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .


UNREELING DIRECTION






NOTE 1. 1 REEL : 1000 CONNECTORS
2 NUMBER OF CONTACTS
3 EXISTENCE
×:PRODUCED, -:NO PRODUCED

REEL DIMENSION





DETAIL OF TAPE FOR VACUUM PICKUP(5:1)

△1 DIMENSION TABLE OF EMBOSSED CARRIER TAPE AND REEL.

PART No.	CODE No.	2	3	A	B	C	D	E	F
FX8C- 60P-SV1(93)	CL578-0521-6-93	60	×	20	25	20.2	40.4	44	44.4
FX8C- 80P-SV1(93)	CL578-0523-1-93	80	×	26	31	20.2	40.4	44	44.4
FX8C-100P-SV1(93)	CL578-0525-7-93	100	—	32	37	26.2	52.4	56	56.4
FX8C-120P-SV1(93)	CL578-0526-0-93	120	—	38	43	26.2	52.4	56	56.4
FX8C-140P-SV1(93)	CL578-0527-2-93	140	—	44	49	34.2	68.4	72	72.4

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
2	POLYESTER	(TOP COVER TAPE)	4	POLYIMIDE	(TAPE FOR VACUUM PICKUP)
1	PS △1	(EMBOSSED CARRIER TAPE)	3		(CONNECTOR)

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	S.SUZUKI	K.NAKAMURA	H.OKAWA	Y.YOSHIMURA	
	03.02.03	03.02.12	03.02.14	03.02.15	. .

TO
PCK

SCALE FREE
UNITS mm

DRAWING NO. EDC3-151087-23

PART NO. FX8C-**P-SV1(93)

HRS HIROSE ELECTRIC CO., LTD

CODE NO. CL578 2/

HRS DRAWING FOR REFERENCE