



In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.
Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.


HRS DRAWING FOR REFERENCE

















NOTE 1 LEAD CO—PLANARITY IS 0.1mm MAX.
2 CONTACTS ARE 3 STEPS SEQUENTIAL. (MF CONTACT A=>SIGNAL CONTACT=>MF CONTACT B)
WHEN USING THIS SEQUENTIAL STRUCTURE, PLEASE AVOID ANGLED INSERTION.
3 MF CONTACT A AND MF CONTACT B CAN BE USED AS POWER SUPPLY CONTACT. (3A/PIN MAX)
4 IT SHOWS THE VACUUM PICKUP AREA. (SEE PAGE 2)
REMOVE THE MYLAR TAPE BEFORE MATING CONNECTORS.
5 PACKING FOR PRODUCT APPLIES EMBOSSED CARRIER TAPE PACKING. (400pcs/RL)
6 BLEMISH AND HIT MARK CAN BE OCCURED THROUGH OUT THE MANUFACTURING PROCESS WHICH DOESN' T AFFECT QUALITY LEVEL.
7 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCES.
1 8 SOLDERING LEAD OF MF CONTACT A SPLITS INTO TWO POLES.
BE SURE TO CONNECT TO THE SAME CIRCUIT.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm LEAD AREA:TIN-PLATING 1μm UNDER PLATING:NICKEL 1.3μm	7	POLYIMIDE	
			6	POLYESTER	(EMBOSSED COVER TAPE)
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm LEAD AREA:GOLD 0.03μm UNDER PLATING:NICKEL 1.3μm	5	POLYSTYRENE	(EMBOSSED CARRIER TAPE)
			4	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm LEAD AREA:TIN-PLATING 1μm UNDER PLATING:NICKEL 1.3μm
1	POLYAMIDE	BLACK UL94V-0			

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	4	DIS-F-005578	TH. SANO	KI. HIROKAWA	11.07.21

HIROSE ELECTRIC CO., LTD.


APPROVED	HS. OKAWA	10.05.10
CHECED	KI. HIROKAWA	10.05.10
DESIGNED	TH. SANO	10.05.10
DRAWN	TH. SANO	10.05.10


DRAWING NO.	EDC3-159561-02
PART NO.	FX18-60P-0.8SV(11)
CODE NO.	CL579-0017-2-11

1 1/2


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

5 DRAWING FOR PACKING (2:1)







REELING DIMENSION(FREE)



1 8 CONFIGURATION OF MF CONTACT A



RECOMMENDED LAND PATTERN DIMENSION OF PCB(2:1)
(PCB THICKNESS: t=1.6mm METAL MASK THICKNESS: t=0.12mm)



HRS DRAWING FOR REFERENCE

図番：	EDC3-159561-02
製品名：	FX18-60P-0.8SV(11)
製品コード	CL579-0017-2-11

△ 2/2