APPLICABLE STANDARD														
OPERATING TEMPERATURE RANGE		-30 °C	то	60 °C (1)		STORAGE RANGE	HUMIDIT	ГҮ	40 %	то	70 % °)		
RATING	STORAGE TEMPERATURE RANGE		-10 °C	то	60 °C (1))								
	OPERATING HI RANGE	JMIDITY	40 %	то	80 %.									
	•		•	SF	PECIFI	CATIO	ONS							
IT	 EM		TEST N					RE	QU	IREMENTS		1	QT	ΑT
CONSTRUCTION														
GENERAL EXAMINATION VISUALL			Y AND BY MEASURING INSTRUM			UMENT.	NT. ACCORDING TO DI			RAWING.			0	0
COUN	T DE	SCRIPTI	ON OF REVISIO	NS.		DE	SIGNED	I		CHECKE	<u> </u>		DAT	
10		-501111 11	2.1 01 NEVIOIOI			- DE	.5.5.112			STILOTEL	-		ادرو	
REMARK (1) THIS STORAGE INDICAT								APPRO	VED	HS.OKA	ΔWA		06.10	1.17
FOR THE UNUSED PROD			OUCT BEFORE THE BOARD MOUNTED.					CHECKED		HS.OZ/		06.10.1		
								DESIG		KY.NAKA		-	06.10	
								DRAV	۷N	AK.SUZU			6.10	
Note QT:Q	ualification Test	urance Test X:Applicable Test				DRAWING					21374-00			
HS	SI	PECIFI	CIFICATION SHEET				ART NO.		A3-GPIN(A)					
HIROSE			LECTRIC CO., LTD.			CC	DDE NO.	CL	CL621-0178-2-00				1	1/1