



- NOTE.
- 1 Mounting side is mated with the receptacle: IT3M-100S-BGA(**) and fixed with the latch.
 - 2 Lot No. shall be marked on the indicated position.
 - 3 The indicated mother board and daughter card shall be fastened to the additional reinforcements to prevent the stress on IT3*-100S-BGA(**) solder joints.
 - 4 Please refer to HIROSE document: ETAD-F0347 'IT3 design guideline'.
 - 5 This product consists of 100 signal lines and 90 ground lines.
 - 6 50pcs of this products are packed in a soft tray.
 - 7 Standard package of 50pcs are packaged in a carton box.

3	LCP	BLACK	UL94V-0						
2	LCP	GRAY	UL94V-0	5	Copper Alloy	CONTACT AREA: NICKEL(1.5 μm) + GOLD (0.76 μm)			
1	PBT	BLACK	UL94V-0	4	Copper Alloy	CONTACT AREA: NICKEL(1.5 μm) + GOLD (0.76 μm)			
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS		
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS			DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.			APPROVED	: MK. EZAKI	15.08.26	DRAWING NO.	EDC-349919-04-00		
			CHECKED	: MK. EZAKI	15.08.26	PART NO.	IT3-100P-32H(04)		
			DESIGNED	: TF. SUGAWARA	15.08.26	CODE NO.	CL636-0266-7-04		
			DRAWN	: KT. AIZAWA	15.08.26				