



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


HRS DRAWING FOR REFERENCE













⚠1 Recommended Footprint design (2:1)





⚠1 12 Recommended Stencil design (2:1)
(Stancil thickness : 0.12mm)

Solder Paste



⚠1 12 Recommended Solder Preform (2:1)
- Quantity : 4pcs/TH (8pcs/Conn)
- Individual Size : 3.2 x 1.6 x 0.8
- Position :See below





Note.
1. The lot number is marked in this area. It may be marked on one or both areas.
2. This area is vacuum pickup area.
3. The dimensions in parentheses are for reference.
4. Manufacturing process could leave scratch and/or punch marks, but they have no effect on the product performance. And the dark spots might occasionally occur on molded plastic.
5. Since silver plating is used for this product, if it is left in the atmosphere for a long time, plating may become drab.
6. Since this product is point symmetry, direction of mounting does not have a rule.
7. This product is RoHS compliant.
8. Please do not mount other devices in this area.
9. Please do not mount devices higher than 4 mm in this area. Otherwise, the devices become obstacles when removing the interposer.
10. Packing for this product is embossed carrier tape packing. (250pcs/RL)
⚠1 11. The insertion direction of a connector may change.
⚠1 12. The connector can be soldered using two step stencil printing process. Please print with a stencil first, and then place solder preforms for complete and consistent soldering. For more detail on this process, please refer to the design guide (ETAD-F0804-00).

NO.	MATERIAL	FINISH , REMARKS
2	Brass	Over Plating : Silver 5.1μm Under Plating : Nickel 1.3μm
1	LCP	Black UL94V-0

NO.	MATERIAL	FINISH , REMARKS
5	Polyester	(Top Cover Tape)
4	Polystyrene	(Embossed Carrier Tape)
3	Capper alloy	Contact Area : Gold 0.76μm Under Plating : Nickel 1.3μm


UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	⚠1	7	DIS-F-00003882	AS. MATSUZAWA	MK. EZAKI	20181030

HIROSE ELECTRIC CO., LTD.


APPROVED	HS. OKAWA	20111216	DRAWING NO. EDC-339733-00-00
CHECKED	KI. HIROKAWA	20111215	PART NO. IT-PM-2S-DIR
DESIGNED	KN. SHIBUYA	20111215	
DRAWN	KN. SHIBUYA	20111215	CODE NO. CL636-0600-7-00 ⚠1 1/2


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Drawing For Packing (Free)



Reeling Dimention (Free)





HRS DRAWING FOR REFERENCE

⚠1 Delete

HRS	DRAWING NO.	EDC-339733-00-00
	PART NO.	IT-PM-2S-DIR
	CODE NO.	CL636-0600-7-00 ⚠1 2/2