


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.










MATING FIGURE



HRS DRAWING FOR REFERENCE

NOTES
1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
2. STIFFENER IS REQUIRED FOR MOUNTING ONTO FPC IN ORDER TO AVOID STRESS BY FPC SLACKING TO MOUNTED CONNECTOR.
3. LOT No. INFORMATION IS SHOWN IN THE TABLE.
   EXAMPLE:9GFD
   →YEAR:2009 MONTH:July DAY:15 LINE No.:4
4. UNMATING SHALL BE DONE WITH THE SPECIFIC EXTRACTION TOOL.

3

YEAR		MONTH		DAY						LINE No.	
YEAR	CODE	MONTH	CODE	DAY	CODE	DAY	CODE	DAY	CODE	LINE No.	CODE
10	0	Jan	A	1	1	11	B	21	M	1	A
11	1	Feb	B	2	2	12	C	22	N	2	B
12	2	Mar	C	3	3	13	D	23	P	3	C
13	3	Apr	D	4	4	14	E	24	Q	4	D
14	4	May	E	5	5	15	F	25	R	5	E
15	5	Jun	F	6	6	16	G	26	S	6	F
16	6	Jul	G	7	7	17	H	27	T	7	G
17	7	Aug	H	8	8	18	J	28	U	8	H
18	8	Sep	I	9	9	19	K	29	V	9	I
09	9	Oct	J	10	A	20	L	30	W	10	J
		Nov	K					31	X		
		Dec	L								

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	PHOSPHOR BRONZE	WHOLE AREA : Gold PLATING 0.1μm min UNDER PLATING : Nickel PLATING 2μm min	7	PS	BLACK
			6	POLYESTER	CLEAR
2	LCP	UL94V-0 , BLACK	5	PS	CLEAR
1	PHOSPHOR BRONZE	CONTACT AREA : Gold PLATING 0.3μm min LEAD AREA : Gold PLATING 0.1μm min UNDER PLATING : Nickel PLATING 2μm min	4	PHOSPHOR BRONZE	WHOLE AREA : Gold PLATING 0.1μm min UNDER PLATING : Nickel PLATING 2μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△					


HIROSE ELECTRIC CO., LTD.

APPROVED	KH. IKEDA	14.11.06
CHECED	MH. TSUCHIDA	14.11.06
DESIGNED	IO. DENPOUYA	14.11.06
DRAWN	YJ. HAGA	14.10.23


DRAWING NO.	EDC3-312852-03
PART NO.	DF36-25S-0.4V(55)
CODE NO.	CL662-4005-1-55

△ 1/2


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



DIRECTION OF UNREELING



STYLE AND DIMENSION OF REEL (FREE)




DETAIL OF PART No. LABEL


生産月日	年　月　日
製品コード	CL662-4005-1-55
製　品　名	DF36-25S-0.4V(55)
納入数量	500pcs
納入者	ヒロセ電機(株)

SUPPLIER
QUANTITY
PART No.
CODE No.
DATE OF MANUFACTURED

6 TAPING (FREE)



RECOMMENDED PATTERN



GROUND AREA

RECOMMENDED METAL MASK

THICKNESS: 0.1mm
OPENING RATIO: LEAD AREA 90%
GROUND AREA 90%

NOTES 5. PER REEL: 500 COMPONENTS.
6 REFER TO JIS C 0806. (PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING)
7. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

HRS DRAWING FOR REFERENCE

DRAWING NO.	EDC3-312852-03
PART NO.	DF36-25S-0.4V(55)
CODE NO.	CL662-4005-1-55

△ 2/2