




Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.











HRS DRAWING FOR REFERENCE

NOTE 1 AVOID ANGLED INSERTION OF CRIMP CONTACT(DF57-****SCF) TO MAINTAIN PERFORMANCE RELIABILITY.

部番	材質	処理，備考
1	PBT	UL94V-0, NATURAL(WHITE)

UNITS mm	SCALE 20：1	△の数	訂正記事	設計	検図	年月日
		△				

HIROSE ELECTRIC CO., LTD.

承認	KI. AKIYAMA	12.03.19
検図	HK. UMEHARA	12.03.19
設計	TS. KUMAZAWA	12.03.19
製図	TS. KUMAZAWA	12.03.19

図番：	EDC3-343901-00
製品名：	DF57H-4S-1.2C
製品コード	CL666-0101-9-00


△ 1/2

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


DF57 Series Mating / Unmating Operation Instruction

Mating


①By positioning the convexity of the socket sides to the header concavity, align the centers of the socket and the header in pitch direction.



②Slightly press the socket down at cable side to tilted angle.




③Press down at the lever side with stabilizing the cable side to insert. Mating completes.




HRS DRAWING FOR REFERENCE

Unmating


①Hook the lever with finger nail.



②Lift up to the upper difrection and friction lock is released.



③Lift up to the upper direction and positive lock is released. Removal completes.



DRAWING NO.	EDC3-343901-00
PART NO.	DF57H-4S-1.2C
CODE NO.	CL666-0101-9-00

△ 2/2