






PART No.	CODE No.	A	B
DF5A-4DP-5DSA (35)	CL676-0029-0-35	-	12.5
DF5A-6DP-5DSA (35)	CL676-0030-0-35	10.0	17.5
DF5A-8DP-5DSA (35)	CL676-0031-2-35	15.0	22.5
DF5A-10DP-5DSA (35)	CL676-0032-5-35	20.0	27.5
DF5A-12DP-5DSA (35)	CL676-0033-8-35	25.0	32.5
DF5A-14DP-5DSA (35)	CL676-0034-0-35	30.0	37.5
DF5A-16DP-5DSA (35)	CL676-0035-3-35	35.0	42.5

APPLICATION DIAGRAM



RECOMMENDED PCB LAYOUT ($t=1.6 \pm 0.1$)



			2		BRASS		SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL PLATED 0.5μm min		
1	POLYAMIDE	NATURAL (BEIGE)・UL94V-0							
NO.	MATERIAL	FINISH , REMARKS			NO.	MATERIAL	FINISH , REMARKS		
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA		15.08.08	DRAWING NO.		EDC-302829-35-01		
		CHECKED : TS. FUKUSHIMA		15.08.08	PART NO.		DF5A- *DP-5DSA(35)		
		DESIGNED : TS. KUMAZAWA		15.08.08	CODE NO.		CL676		
		DRAWN : TS. KUMAZAWA		15.08.08					
									1/