



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.











APPLICATION DIAGRAM



RECOMMENDED PCB LAYOUT(t=1.6±0.1)



PART No.	CODE No.	A	B
DF5A-4DP-5DSA(35)	CL676-0029-0-35	-	12.5
DF5A-6DP-5DSA(35)	CL676-0030-0-35	10.0	17.5
DF5A-8DP-5DSA(35)	CL676-0031-2-35	15.0	22.5
DF5A-10DP-5DSA(35)	CL676-0032-5-35	20.0	27.5
DF5A-12DP-5DSA(35)	CL676-0033-8-35	25.0	32.5
DF5A-14DP-5DSA(35)	CL676-0034-0-35	30.0	37.5
DF5A-16DP-5DSA(35)	CL676-0035-3-35	35.0	42.5

HRS DRAWING FOR REFERENCE

NO.	MATERIAL	FINISH . REMARKS
1	POLYAMIDE	NATURAL(BEIGE). UL94V-0
2	BRASS	SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL PLATED 0.5μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△0					

HRS HIROSE ELECTRIC CO., LTD.

APPROVED	KI. AKIYAMA	15.08.08
CHECKED	TS. FUKUSHIMA	15.08.08
DESIGNED	TS. KUMAZAWA	15.08.08
DRAWN	TS. KUMAZAWA	15.08.08

DRAWING NO.	EDC-302829-35-01
PART NO.	DF5A-*DP-5DSA(35)
CODE NO.	CL676

△0 1/1