

APPLICABLE STANDARD							
RATING	OPERATING TEMPERATURE RANGE		-35°C TO +85°C (NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C (NOTE 3)		
	OPERATING HUMIDITY RANGE		40% TO 80% (NOTE 2)	STORAGE HUMIDITY RANGE	40% TO 70% (NOTE 3)		
	VOLTAGE		500V AC/DC	APPLICABLE CABLE	UL1007, AWG20—22		
	CURRENT	AWG 20 AWG 22	5A	APPLICABLE CONTACT	DF33A-2022SC (F)		
							
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
MARKING		CONFIRMED VISUALLY.				X	X
ELECTRIC CHARACTERISTICS							
INSULATION RESISTANCE		500V DC.		1000MΩ MIN.		X	—
VOLTAGE PROOF		1500V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		X	—
MECHANICAL CHARACTERISTICS							
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.		NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLE FOR EACH, FOR 3 DIRECTIONS.		NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				X	—
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.		① INSULATION RESISTANCE: 500MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55→+85°C TIME 30→ 30min. UNDER 5 CYCLES. THE TRANSFERRING TIME OF THE TANK IS 2~3 min.		① INSULATION RESISTANCE: 1000MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
REMARKS							
NOTE 1:INCLUDING THE TEMPERATURE RISE BY CURRENT.							
NOTE 2:NO CONDENSING							
NOTE3:APPLY TO THE CONDITION OF LONGTERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD, AFTER PCB BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.							
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE		
	1	DIS-H-007821	HT. SATO	TS. KUMAZAWA	13. 04. 25		
Unless otherwise specifid , refer to JIS C 5402.				APPROVED	KI. AKIYAMA	12. 11. 14	
				CHECKED	HK. UMEHARA	12. 11. 13	
				DESIGNED	HT. SATO	12. 11. 13	
				DRAWN	MI. SAKIMURA	12. 11. 13	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-338428-01		
	SPECIFICATION SHEET		PART NO.	DF33C-5S-3. 3C			
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL676-1139-4-00		1/1	