





Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




- Notes 1. Per tray : 96 Pieces.
2. UL(File No.E52653)
C-UL(File No.E52653)
TUV(Certificate No.R50244085) authorization article.




Lot No. is displayed in one of the two locations.



Recommended PCB Layout
(Board thickness: $t=1.6 \pm 0.1\text{mm}$)



Application Diagram



Packing Diagram (FREE)



1	PBT	Red. UL94-V0	3	PS	Clear
NO.	MATERIAL	FINISH . REMARKS	NO.	Copper alloy	Contact Area : Au Plating 0.2μm min Lead Area : Tin Plating 1μm min Under Plating : Ni Plating 1μm min
UNITS mm		SCALE 2 : 1	COUNT 3	DESCRIPTION OF REVISIONS DIS-H-00011936	DESIGNED TS.MIYAKI
HRS HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA 20151128	DRAWING NO. EDC-338974-45-00		
		CHECKED : TS. FUKUSHIMA 20151128	PART NO. DF60-2P-10.16DSA(45)		
		DESIGNED : TS. KUMAZAWA 20151128	CODE NO. CL0680-3005-8-45		
		DRAWN : TS. KUMAZAWA 20151128	DATE 20220125		