

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


HRS DRAWING FOR REFERENCE



APPLICATION DIAGRAM(10:1)



4 RECOMMENDED PATTERN(FREE)



NOTES 1 :LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
2 :IF SOLDERING PADS IS LONG, THERE IS A POSSIBILITY THAT IT WILL MAKE CONTACT WITH THE METAL SHELL.
3 :IF THERE IS PATTERN ON ▨ PART, THERE IS A POSSIBILITY THAT IT WILL MAKE CONTACT WITH THE METAL SHELL.
4 :RECOMMENDED THICKNESS OF CREAM SOLDER PASTE:0.15mm
OPEN AREA RATIO:100%

NO.	MATERIAL	FINISH, REMARKS
2	PHOSPHOR BRONZE	LEAD AREA:TIN PLATED 1μm min 5 UNDER PLATING:NICKEL PLATED 0.5μm min
1	POLYAMIDE	BLACK, UL94V-0

NO.	MATERIAL	FINISH, REMARKS
5	POLYESTER	CLEAR(COVER TAPE)
4	PS	CLEAR(EMBOSSED CARRIER TAPE)
3	PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATED 0.1μm min LEAD AREA:TIN-COPPER PLATED 1μm min UNDER PLATING:NICKEL PLATED 1μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△					


HIROSE ELECTRIC CO., LTD.


APPROVED	HK. UMEHARA	11.10.03
CHECKED	HK. UMEHARA	11.10.03
DESIGNED	HT. SATO	11.10.03
DRAWN	MI. SAKIMURA	11.09.29


DRAWING NO.	EDC3-162021-03
PART NO.	DF19G-14P-1H(54)
CODE NO.	CL685-0004-0-54


△ 1/2


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.











SUPPLIER
QUANTITY
PART No.
CODE No.
DATE OF MANUFACTURED

DETAIL OF PART No. LABEL

生産月日	年　月　日
図番	CL0685-0004-0-54
品名	DF19G-14P-1H(54)
納入数量	1000Ko
納入者	ヒロセ電機株式会社

NOTES 6 : 1 REEL 1000 CONNECTORS.
7 : AT THE BEGINNING OF THE REEL, 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.

HRS DRAWING FOR REFERENCE

HRS	DRAWING NO.	EDC3-162021-03
	PART NO.	DF19G-14P-1H(54)
	CODE NO.	CL685-0004-0-54 △ 2/2