Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C(NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C
	VOLTAGE	100 V AC	APPLICABLE CONNECTOR	DF19*-20P-1H(56)
	CURRENT	0.5 A		

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	○	○
MARKING	CONFIRMED VISUALLY.		○	○

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0					

REMARKS
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.
NOTE2:*=TERMINATION STYLE MARKING
(C:CRIMP SOCKET, F:FPC SOCKET, SD:SOCKET FOR FINE COAXIAL CABLES)
Unless otherwise specified, refer to JIS C 5402.

APPROVED	TY.OMA	05.11.04
CHECKED	HK.UMEHARA	05.10.31
DESIGNED	TS.KUMAZAWA	05.10.31
DRAWN	AH.MIYAZAKI	05.10.31

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-162455-02

HRS

SPECIFICATION SHEET

HIROSE ELECTRIC CO., LTD.

PART NO. DF19G-20S-1F-GND(05)

CODE NO. CL685-0010-3-05 0 1/1

FORM HD0011-2-1