










APPLICATION DIAGRAM(FREE)



RECOMMENDED PATTERN(FREE)




PART NO.	HRS NO.	NUMBER OF CONTACTS	A	B	C
DF20F-10DP-1V(55)	CL686-0032-2-55	10	4.0	7.3	6.6
DF20F-20DP-1V(55)	CL686-0033-5-55	20	9.0	12.3	11.6
DF20F-30DP-1V(55)	CL686-0034-8-55	30	14.0	17.3	16.6
DF20F-40DP-1V(55)	CL686-0035-0-55	40	19.0	22.3	21.6
DF20F-50DP-1V(55)	CL686-0036-3-55	50	24.0	27.3	26.6

NOTES1:LEAD CO-PLANARITY SHALL BE 0.1mm MAX INCLUDING METAL HOLD DOWN.


2 IF THERE IS PATTERN ON PART, THERE IS A POSSIBILITY THAT IT WILL MAKE CONTACT WITH THE LEADS.

3 THE NUMBER AND POSITION OF A RIB ARE AS FOLLOWS BY THE NUMBER OF CONTACTS.


10, 20DP



30, 40DP




50DP



2	PHOSPHER BRONZE	Contact Area:Gold Plated 0.2μm min.	5	S. PVC	STOPPER, GRAY
		Lead Area:Gold Plated 0.015μm min.	4	PC-M	ELECTROSTATIC PROTECTION, CLEAR
		Under Plating:Nickel Plated 2μm min.	3	BRASS	Surface:Tin-Copper Plated 1μm min.
1	POLYAMIDE	NATURAL (BEIGE), UL94V-0			Under Plating:Nickel Plated 1μm min.
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
UNITS mm		SCALE 5 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-H-008680	
HIROSE ELECTRIC CO., LTD.		APPROVED : TY. OMA	06.02.06	DRAWING NO.	EDC3-164529-03
		CHECKED : HK. UMEHARA	06.02.04	PART NO.	DF20F-*DP-1V(55)
		DESIGNED : SZ. ONO	06.02.03	CODE NO.	CL686-
		DRAWN : SZ. ONO	06.02.03		
		DESIGNED	MI. SAKIMURA	CHECKED	TS. FUKUSHIMA
		DATE	14.04.11		

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





DRAWING NO.	EDC3-164529-03		
PART NO.	DF20F- * DP-1V(55)		
CODE NO.	CL686-		