
Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



HRS DRAWING FOR REFERENCE

NOTE 1. The procedure of cable assemblies would be confirm.
2. When this plug is mated with a MF10S receptacle, the clamp torque of the part No.⑫ should be 1.5 to 3 N·m. Following MF10-T1 can be used as simple substitution of a torque wrench.

EXCLUSIVE PLASTIC SPANNER	PART NO.	CODE NO.
	MF10-T1	CL709-0205-8

3 The ferrule parts are not contained. Please use the "standard MU ferrule" chosen from the outer diameter of the optical fiber.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
7	BRASS	CHROME PLATING	14	ZIRCONIA	———
6	NBR RUBBER	COLOR:BLACK	13	STAINLESS STEEL	———
5	NBR RUBBER	COLOR:BLACK	12	STAINLESS STEEL	NYELOCK
4	ZINC DIECAST	NICKEL PLATING	11	ALUMINIUM ALLOY	ANODIC OXIDE COATING
3	ALUMINIUM ALLOY	ANODIC OXIDE COATING	10	STAINLESS STEEL	———
2	BRASS	CHROME PLATING	9	PPS RESIN	COLOR:BLACK
1	ZINC DIECAST	CHROME PLATING	8	NBR RUBBER	COLOR:BLACK

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△0					

HRS HIROSE ELECTRIC CO., LTD.

APPROVED	MT. SHIBUTANI	18.02.01	DRAWING NO. EDC-178122-31-00
CHECKED	FS. YOSHIDA	18.02.01	PART NO. MF10S-WP7C50-0200(31)
DESIGNED	TY. SATO	18.02.01	CODE NO. CL709-0211-0-31 △0 1/1
DRAWN	MK. INOUE	18.02.01	