Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE







B−B





NOTE
1. These dimensions indicate the condition after cable assembly.
2. Ferrules are not included in this product. MU ferrules are separately available.
3. Recommended tightening torque is 3N・m.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
6	BRASS	NICKEL PLATING			
5	BRASS	NICKEL PLATING	11	BRASS	CHROME PLATING (BLACK)
4	BRASS	NICKEL PLATING	10	BRASS	CHROME PLATING (BLACK)
3	PIANO WIRE	ZINC PLATING + BAKING	9	SYNTHETIC RUBBER (SiR)	COLOR : BLACK
2	SYNTHETIC RUBBER (CR)	COLOR : BLACK	8	STAINLESS STEEL	———
1	ZINC DIE CASTING	CHROME PLATING (BLACK)	7	SYNTHETIC RESIN (TPEE)	COLOR : MAUVE

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	0				

HIROSE ELECTRIC CO., LTD.

APPROVED	MT. SHIBUTANI	18.02.02
CHECKED	FS. YOSHIDA	18.02.02
DESIGNED	TY. SATO	18.02.02
DRAWN	MK. INOUE	18.02.02

DRAWING NO.	EDC-177418-31-00
PART NO.	MF10B-WRBCH01-0200(31)
CODE NO.	CL709-1033-0-31

0 1/1