


Sep. 1. 2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURES RANGE	-30°C TO 105°C (SOT-14)			STORAGE TEMPERATURE RANGE	-40°C TO +105°C			
	VOLTAGE	250 V AC			CURRENT	3 A			
<b>SPECIFICATIONS</b>									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
<b>CONSTRUCTION</b>									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			<input type="checkbox"/>	<input type="checkbox"/>
MARKING		CONFIRMED VISUALLY.						<input type="checkbox"/>	<input type="checkbox"/>
<b>ELECTRICAL CHARACTERISTICS</b>									
CONTACT RESISTANCE		1 A DC.			30 mΩ MAX.			<input type="checkbox"/>	<input type="checkbox"/>
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV AC MAX, 0.1 mA(DC OR 1000 Hz)			30 mΩ MAX.			<input type="checkbox"/>	<input type="checkbox"/>
INSULATION RESISTANCE		—— V DC			100 MΩ MIN.			<input type="checkbox"/>	<input type="checkbox"/>
VOLTAGE PROOF		—— V AC FOR 1 MIN			NO FLASHOVER OR BREAKDOWN.			<input type="checkbox"/>	<input type="checkbox"/>
<b>MECHANICAL CHARACTERISTICS</b>									
CONTACT INSERTION AND EXTRACTION FORCES		—— BY STEEL GAUGE.			INSERTION FORCE —— N MAX. EXTRACTION FORCE —— N MIN.			<input type="checkbox"/>	<input type="checkbox"/>
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 60 mΩ MAX. ② NO DAMAGE. CRACK AND LOOSENESS OF PARTS.			<input type="checkbox"/>	<input type="checkbox"/>
VIBRATION		FREQUENCY 20 TO 200 Hz, 43.1 m/S <sup>2</sup> AT 3 h FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② CONTACT RESISTANCE: 60 mΩ MAX. ③ NO DAMAGE. CRACK AND LOOSENESS OF PARTS.			<input type="checkbox"/>	<input type="checkbox"/>
SHOCK		FREQUENCY 20 TO 50 Hz, 66.6 m/S <sup>2</sup> AT 1 h			① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② CONTACT RESISTANCE: 60 mΩ MAX. ③ NO DAMAGE. CRACK AND LOOSENESS OF PARTS.			<input type="checkbox"/>	<input type="checkbox"/>
LOCK STRENGTH		APPLYING A PULL FORCE THE MATING AXIALLY AT —— N MAX.			① DURING APPLYING, MATING COMPLETELY. ② AFTER APPLYING, NO DEFECT OF MATING PARTS.			<input type="checkbox"/>	<input type="checkbox"/>
<b>ENVIRONMENTAL CHARACTERISTICS</b>									
DAMP HEAT (STEADY STATE)		EXPOSED AT 60 °C, 90 TO 95 %, 500 h.			① CONTACT RESISTANCE: 60 mΩ MAX. ② INSULATION RESISTANCE: 100MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			<input type="checkbox"/>	<input type="checkbox"/>
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -40 → 5 TO 35 → 85 → 5 TO 35 °C TIME 30 → 5 → 30 → 5 MIN UNDER 1000 CYCLES.			① CONTACT RESISTANCE: 60 mΩ MAX. ② INSULATION RESISTANCE: 100MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PART.			<input type="checkbox"/>	<input type="checkbox"/>
DRY HEAT		EXPOSED AT 105 °C, 300 h.			① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.			<input type="checkbox"/>	<input type="checkbox"/>
COLD		EXPOSED AT -55 °C, 120 h.			① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.			<input type="checkbox"/>	<input type="checkbox"/>
CORROSION, SALT MIST		EXPOSED IN 5% SALT WATER SPRAY FOR 96 h.			① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.			<input type="checkbox"/>	<input type="checkbox"/>
RESISTANCE TO H <sub>2</sub> S <sup>+</sup> GAS		EXPOSED IN 500 PPM FOR 8 h.			① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.			<input type="checkbox"/>	<input type="checkbox"/>
RESISTANCE TO SOLDERING HEAT		SOLDER TEMPERATURE, 260 °C FOR IMMERSION, DURATION, 10 s.			NO DEFORMATION IN CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.			<input type="checkbox"/>	<input type="checkbox"/>
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, 230 °C FOR IMMERSION DURATION, 3 S			A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.			<input type="checkbox"/>	<input type="checkbox"/>
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVD	RELEASED	
NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT.				T. SHISHIKURA '01.6.12	T. SHISHIKURA '01.6.12	N. NAKATA '01.6.13	K. Sato '01.6.13		
Note QT:Qualification Test AT:Assurance Test ○:Applicable Test									
 HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET			PART NO. GT17VS-10DS-SC				
CODE NO. (OLD)		DRAWING NO. ELC4-165728			CODE NO. CL767-0060-8			1	1