Aug.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE
△						△					
△						△					

APPLICABLE STANDARD

RATING				
	ELECTRIC SOURCE	PHASE ~~AC・DC~~ V Hz	WEIGHT	5kg
	DISSIPATION POWER		APPLICABEL CONNECTOR	3130-8P-C
	AIR SOURCE		APPLICABLE CABLE	
	AIR CONSUMPTION			
	OPERATING TEMPERATURE LIMIT	°C~ °C	APPLICABLE EQUIPMENT	Hi-Flex CONNECTION PRESS HHP502 CL550-0082-2

SPECIFICATIONS

CONSTITUTION

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
APPEARANCE, STRUCTURE AND FINISH	Visually and by measuring instrument.	According to drawing.	○	○
MARKING	Confirmed visually.	According to drawing.	○	○

REMARKS

Unless otherwise specified, refer to

DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
11.6.30 H.KUDO	11.6.30 H.YANAGISAWA	11.6.30 H.Shimada	11.6.30 S.Sakurai	

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

TO
PE

HRS HIROSE ELECTRIC CO.,LTD. | SPECIFICATION SHEET | PART NO. 3130-8CT

CODE NO. (OLD)	DRAWING NO. ELC4- 080619	CODE NO. CL 902-0287-4	1/1

FROM001-1