

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE
△	1	DIS-P-00000406	KUDO	TOKUTA	19.1.24	△					
△						△					
APPLICABLE STANDARD											
RATING	ELECTRIC SOURCE		PHASE AC-DC V Hz			WEIGHT		△ 50g			
	DISSIPATION POWER					APPLICABLE CONNECTOR		DH30B-37S			
	AIR SOURCE					APPLICABLE CABLE					
	AIR CONSUMPTION					APPLICABLE EQUIPMENT		DH/IDCK-MP CL902-2185-5			
	OPERATING TEMPERATURE LIMIT		°C~°C								
SPECIFICATIONS											
CONSTITUTION	ITEM	TEST METHOD				REQUIREMENTS		QT	AT		
	APPEARANCE, STRUCTURE AND FINISH	Visually and by measuring instrument.				According to drawing.		○	○		
	MARKING	Confirmed visually.				According to drawing.		○	○		
REMARKS											
						DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
						11.1.12 H.KUDO	11.1.12 M.TAKAHASHI	11.1.26 M.SHIAMDA	11.1.26 S.SAKABE		
Unless otherwise specified, refer to											
Note QT:Qualification Test AT:Assurance Test X:Applicable Test											
HRS HIROSE ELECTRIC CO.,LTD.						SPECIFICATION SHEET			PART NO. DH-37UNIT		
CODE NO. (OLD)			DRAWING NO. ELC4- 276090			CODE NO. CL 902-2188-3			1 / 1		