<u> </u>	COUNT	DESCRIPTION OF REV	VISIONS	BY	CHECKED	DATE		COUNT	DESCRIPTION	OF REVISIONS	BY	CHECKED	DATE
\sqrt{V}	1_1_	DIS-P-0000	0406	KUDO	TOKUTA	19.1.24	\triangle						
							\triangle						
ΑP	PLIC/	ABLE STAND	ARD										
		ELECTRIC SOL	ELECTRIC SOURCE				Hz WEIGHT				100g		
		DISSIPATION POWER					APPLICABI		EL CONNECTOR		DH-37-CMB(8.8)		
RA	TING	AIR SOURCE					APPLICABLE CABLE						
		AIR CONSUMPTION							LE CABLE				
		OPERATING		°C~°C						DH/IDCK-	MP		
		TEMPERATURE	LIMIT	I IA			APH	APPLICABLE EQUIPMENT		ENT		CL902-2	185-5
		<u>.1</u>		SPECIFICATIO				NS		<u>I</u>			
\vdash		ITEM	Т	TEST METHOD					REQUIREMEN		NTS QT AT		ΔТ
\vdash	A DDE	ARANCE,	TEST WIETHOD						TREGOTTEME		INTO	QT	Ai
		CTURE AND	Visua	Visually and by measuring instrument.					According to drawing.		ng.	0	0
	MARK	ING	Conf	Confirmed visually.					According to drawing.		0	0	
CONSTITUTION E	MARK								DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
I _	VIFUAL	0							11.1.12	11.1.12	11.1.26	11.1.26	NEELNOLL
Unless otherwise specified, refer to									H KUDO		M SHIMADA		
					^ T. ^			V A ll a	LI- Ta	1.			
Note QT:Qualification Test AT:Assurance Test X:Applicable Test													
H	HIROSE ELECTRIC CO.,LTD. SPECIFICATION									DH-37-CMB(8.8)UNIT			
CODE NO. (OLD)				DRAWING NO. FLC4- 276094				CODE NO.		0.0	002-2192-0		1/,

TO PE