

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE
△						△					
△						△					
APPLICABLE STANDARD											
RATING	ELECTRIC SOURCE	PHASE	AC・DC	V	Hz	WEIGHT		0.5kg			
	DISSIPATION POWER					APPLICABLE CONNECTOR		TM3P-64P TM4P-64P			
	AIR SOURCE					APPLICABLE CABLE					
	AIR CONSUMPTION					APPLICABLE EQUIPMENT					
	OPERATING TEMPERATURE LIMIT	℃~℃									
SPECIFICATIONS											
CONSTITUTION	ITEM	TEST METHOD				REQUIREMENTS		QT	AT		
	APPEARANCE, STRUCTURE AND FINISH	Visually and by measuring instrument.				According to drawing.		○	○		
	MARKING	Confirmed visually.				According to drawing.		○	○		
REMARKS						DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
						16.5.31 H.KUDO	16.5.31 M.TAKAHASHI	16.6.2 H.TOKUTA	16.6.2 T.ITO		
Unless otherwise specified, refer to											
Note    QT:Qualification Test    AT:Assurance Test    X:Applicable Test											
TO		HIROSE ELECTRIC CO.,LTD.				SPECIFICATION SHEET		PART NO. HT601-TM3/4P-64P			
PE		CODE NO. (OLD)				DRAWING NO. ELC- 276478-00-00		CODE NO. CL 902-2206-3		1 / 1	