


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


HRS DRAWING FOR REFERENCE









POLARIZATION MARK
(POLALIZATION MARK SHALL BE PROCESSED BY CHAMFERING.)





A–A

CABLE ASSEMBLY DRAWING



NOTE 1. THE REFERENCE NO. ④, ⑤ AND ⑥ SHALL BE ATTACHED.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	COPPER ALLOY	CONTACT AREA:GOLD PLATING 0.2μm min.	7	STAINLESS STEEL	
		LEAD AREA:GOLD PLATING 0.03μm min. ⚠1	6	POLYCARBONATE	BLACK, UL94HB
2	COPPER ALLOY	UNDER PLATING:NICKEL PLATING 2μm min.	5	PHOSPHOR BRONZE	NICKEL PLATING 1μm min. ⚠1
1	PPS	BLACK, UL94V-0	4	BRASS	NICKEL PLATING 1μm min. ⚠1

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	4 : 1	⚠1	4	DIS-E-003308	TS. ITO	TA. ASO	10.06.14

HIROSE ELECTRIC CO., LTD.

APPROVED	AO. SUZUKI	06.05.22
CHECKED	NF. MIYAZAKI	06.05.22
DESIGNED	HS. KIKUCHI	06.05.22
DRAWN	HS. KIKUCHI	06.05.22

DRAWING NO.	EDC3-045931-03
PART NO.	3240-8P-C(50)
CODE NO.	CL232-0001-4-50 ⚠1 1/1