Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE





Recommended PCB Layout (t=1.6 FR4) Land/Pad Part Resist Part



Note 1. ※ indicates duplicate dimension.
2. This pattern is an example of the FCB.
(thickness=1.6mm, material=FR4, layer thickness containing plating=0.035mm)

Reference:Panel Layout(Thickness 0.5~2.5mm)



Assembled figure (1:1)



Nut (1:1)



Washer (1:1)



Packing specification(FREE) ⚠2



Packing unit:max 250pcs/box
(Max 4 trays /box)

Max 70pcs/tray
(There is some fraction trays)

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	BERYLLIUM COPPER	GOLD PLATING			
2	SPS		5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	NICKEL PLATING	4	BRASS	NICKEL PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	⚠2	1	DIS-D-00001222	MA. SAEKI	KY. SHIMIZU	16. 05. 31

HIROSE ELECTRIC CO., LTD.

APPROVED	KY. SHIMIZU	16. 03. 04	DRAWING NO. EDC-368216-00-00
CHECKED	KY. SHIMIZU	16. 03. 04	PART NO. BNC(75)-BLR-PC-12G
DESIGNED	YI. FUNADA	16. 03. 04	
DRAWN	YI. FUNADA	16. 03. 04	CODE NO. CL302-0081-0-00 ⚠2 1/1