Nov.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.







HRS DRAWING FOR REFERENCE

HRS No.	PART NO.	1 STAMPED CHARACTER	2 APPLICABLE CABLE
CL541-0266-4-06	DF1B-R28A(06)	28	UL1007 AWG28

NOTES 1 INDICATE APPLICABLE CABLE AWG No.
2 JACKET DIAMETER φ0.9 to φ1.39.
3 RANGE OF GOLD PLATED.
4. 1PACK:100 CONNECTORS.

NO.	MATERIAL	FINISH , REMARKS
1	PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATED 0.2μm min OTHER AREA:TIN PLATED 2.0μm min UNDER PLATING:NICKEL PLATED 1.0μm min

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	10:1					

HIROSE ELECTRIC CO., LTD.

APPROVED	KI. AKIYAMA	12.10.22
CHECKED	HK. UMEHARA	12.10.22
DESIGNED	KY. SHIMAKURA	12.10.22
DRAWN	MI. SAKIMURA	12.10.19

DRAWING NO.	EDC3-020660-01
PART NO.	DF1B-R28A(06)
CODE NO.	CL541-0266-4-06

△ 1/1