

Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





RECOMMENDED PCB LAYOUT
(MOUNTING SURFACE SIDE) (FREE)




RECOMMENDED METAL MASK (FREE)


THICKNESS : 0.1mm










MATING FIGURE (5:1)








A(10:1)





HRS DRAWING FOR REFERENCE

NOTES 1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX
△2 ▨ AREA INDICATED MUST BE FREE OF CONDUCTIVE TRACES OR THE CONDUCTIVE TRACES MUST BE COVERED BY RESIST FILM.
3. PLEASE CONSULT HIROSE WHEN THE PRODUCT IS MONUTED TO FPC.

NO.	MATERIAL	FINISH , REMARKS
3	BRASS	CONTACT AREA : Au PLATING 0.05μm MIN LEAD AREA : Au PLATING 0.05μm MIN UNDER PLATING : Ni PLATING 1μm MIN
2	BRASS	CONTACT AREA : Au PLATING 0.05μm MIN LEAD AREA : Au PLATING 0.05μm MIN UNDER PLATING : Ni PLATING 1μm MIN
1	LCP	BLACK , UL94V-0


NO.	MATERIAL	FINISH , REMARKS
8	PS	REEL , BLACK
7	POLYESTER	CLEAR
6	PS	CLEAR
5	STAINLESS STEEL	—
4	BRASS	CONTACT AREA : Sn PLATING 1μm MIN UNDER PLATING : Ni PLATING 0.5μm MIN

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	FREE	△2	5	DIS-H-007735	MI. SAKIMURA	TS. KUMAZAWA	13. 03. 22


HIROSE ELECTRIC CO., LTD.

APPROVED	TS. SAKATA	09. 12. 04	DRAWING NO. EDC3-320002-01
CHECED	MN. KENJO	09. 12. 04	PART NO. DF50-30DP-1V(51)
DESIGNED	TT. OHSAKO	09. 12. 04	CODE NO. CL665-0001-8-51 △2 1/2
DRAWN	TT. OHSAKO	09. 12. 04	


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



B-B(FREE)



② STYLE AND DIMENSION OF REEL (FREE)




DETAIL OF PART No. LABEL


生産月日	年　月　日
図　番	CL665-0001-8-51
品　名	DF50-30DP-1V(51)
納入数量	1000 KO
納入者	ヒロセ電機(株)

SUPPLIER
QUANTITY
PART No.
CODE No.
DATE OF MANUFACTURED


C-C(FREE)



⑤ TAPING (FREE)



REFLOW TEMPERATURE PROFILE USING LEAD-FREE SOLDER PASTE (REFERENCE)



NUMBER OF REFLOW CYCLES 2 CYCLES MAX.
THE TEMPERATURE IS MEASURED IN THE TERMINAL LEAD PART.

ADDITIONAL FACTORS, SUCH AS SOLDER PASTE TYPE, PCB SIZE AND OTHER MOUNTED COMPONENTS COULD AFFECT THE PROFILE, THEREFORE, A THOROUGH EVALUATION OF MOUNTING CONDITION IS REQUIRED PRIOR TO PRODUCTION. TEMPERATURE IS MEASURED AT CONTACT LEAD.

注4. 1 REEL : 1000 CONNECTORS
⑤ REEL TO JIS C 0806.(PACKAGING OF COMPONENTS FOR AUTOMATIC HANDLING)
6. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

HRS DRAWING FOR REFERENCE

HRS	DRAWING NO.	EDC3-320002-01
	PART NO.	DF50-30DP-1V(51)
	CODE NO.	CL665-0001-8-51 ② 2/2