

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .




RECOMMENDED LAND PATTERN DIMENSION OF PCB




HRS DRAWING FOR REFERENCE

CROSS CUT SECTION - SIGNAL (5 : 1)



CROSS CUT SECTION - GROUND (5 : 1)



NOTES 1 10 HATCHED ▨ PARTS: GROUND CIRCUIT.
2 2 HATCHED ▨ PARTS: GROUND CIRCUIT.
3 SMT LEAD-COPLANARITY: 0.1 MAX.
4 THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
5 MAKE SURE WIDTH OF PATTERN IS WITHIN THAT OF LAND, OR LEAD MAY TOUCH PATTERN. (THIS APPLIES TO HATCHED ▨ AREA.)
6 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

NO.	MATERIAL	FINISH, REMARKS
4	PHOSPHOR BRONZE	TIN-PLATING
		CONTACT AREA: GOLD 0.1μm min.
3	PHOSPHOR BRONZE	LEAD AREA : TIN-PLATING 1μm min.
		UNDER PLATING : NICKEL 1μm min.
2	PHOSPHOR BRONZE	TIN-PLATING
1	LCP	BEIGE UL94V-0

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	A. SUZUKAWA '06.09.13	H. Nakamura '06.09.20	K. Ozawa '06.09.21	H. Okawa '06.09.21	. .

SCALE	DRAWING NO.	PART NO.
4 : 1	EDC3-151961-25	FX10A-100P/10-SV1(71)
UNITS mm	HIROSE ELECTRIC CO., LTD	CODE NO. CL570-0102-2-71

TO

1/1