

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .




RECOMMENDED LAND PATTERN DIMENSION OF PCB



CROSS CUT SECTION - SIGNAL (5 : 1)



CROSS CUT SECTION - GROUND (5 : 1)



HRS DRAWING FOR REFERENCE

NOTES 1 10 HATCHED ▨ PARTS: GROUND CIRCUIT.
2 2 HATCHED ▨ PARTS: GROUND CIRCUIT.
3 SMT LEAD-COPLANARITY: 0.1 MAX.
4 THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
5 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
1	LCP	BEIGE UL94V-0	3, 4	PHOSPHOR BRONZE	TIN-PLATING
					CONTACT AREA: GOLD 0.1μm min.
			2	PHOSPHOR BRONZE	LEAD AREA : GOLD FLASH
					UNDER PLATING : NICKEL 1μm min.

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	A.SUZUKAWA '06.09.21	'06.09.21	'06.09.21	'06.09.21	. .

SCALE	DRAWING NO.	PART NO.
4 : 1	EDC3-151977-25	FX10A-100S/10-SV(71)
UNITS mm	HRS HIROSE ELECTRIC CO., LTD	CODE NO. CL570-0202-7-71 1/1

TO