


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



CROSS-CUT SECTION (10:1) 4



RECOMMENDED LAND PATTERN



HRS DRAWING FOR REFERENCE

NOTES

1 SMT LEAD-COPLANARITY: 0.1 MAX.
2 THIS PRODUCT HAS NO POLARITY TO MOUNT ON THE RECOMMENDED LAND PATTERN.
3 NO PATTERN SHALL BE DESIGHNED IN THIS AREA ▨ , TO PREVENT CONTACTS FROM BEING TOUCHED WITH PATTERN.
4 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

NO.	MATERIAL	FINISH, REMARKS
1	LCP	BEIGE UL94V-0
2	PHOSPHOR BRONZE	TIN-PLATING CONTACT AREA : GOLD 0.1μm min. LEAD AREA : TIN-PLATING 1μm min. UNDER PLATING : NICKEL 1μm min.
3	PHOSPHOR BRONZE	TIN-PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	4 : 1	1	1	DIS-F-00012901	SY. KUDO	HT. YAMAGUCHI	20220218

HIROSE ELECTRIC CO., LTD.

APPROVED	HS. OKAWA	20060418
CHECKED	HS. OZAWA	20060418
DESIGNED	KT. DOI	20060417
DRAWN	KT. DOI	20060417

DRAWING NO.	EDC3-151971-25
PART NO.	FX10A-168P-SV1(71)
CODE NO.	CL0570-0144-2-71