



NOTES 1 SMT LEAD-COPLANARITY:0.1 MAX.  
2 THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.  
3 MAKE SURE WIDTH OF PATTERN IS WITHIN THAT OF LAND .OR LEAD MAY TOUCH PATTERN. (THIS APPLIES TO HATCHED AREA.)

2	PHOSPHOR BRONZE	CONTACT AREA: GOLD (0.1μm) OVER NICKEL				
		LEAD: GOLD FLASH OVER NICKEL				
1	LCP	BEIGE	UL94V-0			
NO.	MATERIAL	FINISH, REMARKS	3	PHOSPHOR BRONZE	TIN PLATED	
CODE NO. (OLD)	CL	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
		J. Matsukawa J. Matsukawa J. Matsukawa				
		99.2.12	99.2.12	99.2.12	99.2.12	
DRAWING NO.		PART NO.		FX11LA-116S-SV		
EDC3-152118						
SCALE						
5 : 1						
UNITS	HIROSE ELECTRIC CO., LTD.					
mm	CL573-0144-1					
	1					

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△				..	△				..
△				..	△				..
△				..	△				..

TO	
PCK	