









May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE)



- NOTES 1 LEAD CO-PLANARITY SHALL BE 0.15 MAX.
2 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
3 IN CASE OF THE AUTOMATED MOUNTING, RECOMMENDED HOLE DIAMETER OF BOSS IS SHOWN IN FIG. 1.

			3	BRASS	TIN-PLATING				
1	PPS	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.2#m min.				
					LEAD AREA:TIN-PLATING 2#m min.				
					UNDER PLATING:NICKEL 1.5#m min.				
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS			
UNITS mm			SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED :HS. OKAWA		07. 10. 19		DRAWING NO. EDC3-082415-21			
		CHECED :HS. OZAWA		07. 10. 19		PART NO. FX2-40S-1. 27SVL (71)			
		DESIGNED :SY. KAMIGA		07. 10. 19		CODE NO. CL572-2153-7-71			
		DRAWN :HK. SUNADORI		07. 10. 19		 1/			