






May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



RECOMMENDED PC BOARD HOLE PATTERN (MOUNTING SIDE) t=1.6



- NOTES 1 LOT NO. MARKING SIDE SHALL BE OPTIONAL.
2. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

					3	PHOSPHOR BRONZE	CONTACT AREA : GOLD 0.2μm min.		
							DIP AREA : TIN-PLATING 2μm min.		
							UNDER PLATING : NICKEL 2μm min.		
1. 2. 4	POLYAMIDE	BLACK , UL94V-0							
NO.	MATERIAL	FINISH , REMARKS			NO.	MATERIAL	FINISH , REMARKS		
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA		07. 08. 10	DRAWING NO. EDC3-083212-21				
		CHECED : HS. OZAWA		07. 08. 10	PART NO. FX2C2-32S-1. 27DSA (71)				
		DESIGNED : KY. NAKAMURA		07. 08. 10	CODE NO. CL572-2422-7-71				
		DRAWN : TP. MATSUMOTO		07. 08. 08	 1/1				