






NOTES 1. LEAD CO-PLANARITY INCLUDING REINFORCED METAL FITTINGS TO BE 0.1 MAX.
2. NOTE THAT THE REFERENCE TIGHTENING TORQUE IS 0.15 N·m.
3. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

RECOMMENDED LAND PATTERN DIMENSION OF PCB(MOUNTING SIDE)



A-A (5 : 1)



4	BRASS	TIN-PLATING	2, 3	BRASS	CONTACT AREA: GOLD 0.1μm min.				
1	POLYAMIDE	BEIGE UL94V-0			LEAD AREA: TIN-PLATING 1μm min.				
					UNDER PLATING: NICKEL 1μm min.				
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS			
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED	: HS. OKAWA	07. 10. 30	DRAWING NO. EDC3-151380-21				
		CHECKED	: HS. OZAWA	07. 10. 30	PART NO. FX5-20P-SH(71)				
		DESIGNED	: SY. KAMIGA	07. 10. 30	CODE NO. CL575-0001-7-71				
		DRAWN	: HK. SUNADORI	07. 10. 26					