



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.










A-A(10:1)




HRS DRAWING FOR REFERENCE

NOTE
1. HRS MARK SHALL BE OPTIONAL.
2. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
3. EMBOSSED CARRIER TAPE PACKAGING SHALL BE APPLIED TO THIS PRODUCT. SEE NEXT PAGE FOR DETAILS.
4. THIS PRODUCT HAS TAPE FOR VACUUM PICKUP. SEE NEXT PAGE FOR DETAIL OF STICKING POSITION, ETC.
5. FOR MODIFICATION, ETC, PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
6. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
7. 1 REEL : 1000 CONNECTORS.
8. REMOVE THE VACUUM PICKUP TAPE AFTER MOUNTING THE CONNECTOR.

RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE)

(METAL MASK THICKNESS:t=0.15)



NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min.	5	POLYIMIDE	(TAPE FOR VACUUM PICKUP)
		LEAD AREA:TIN-PLATING 1μm min.	4	POLYESTER	(COVER TAPE)
		UNDER PLATING:NICKEL 2μm min.			
1	PPS	LIGHT BROWN (UL94V-0)	3	POLYSTYRENE	(EMBOSSED CARRIER TAPE)


UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△				


HIROSE ELECTRIC CO., LTD.


APPROVED	HS. OKAWA	13. 08. 28	DRAWING NO. EDC3-156320-02
CHECED	HT. YAMAGUCHI	13. 08. 27	PART NO. FX6A-30S-0.8SV2(93)
DESIGNED	TH. SANO	13. 08. 27	
DRAWN	TH. SANO	13. 08. 27	CODE NO. CL576-0322-7-93 △ 1/2

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


UNREELING DIRECTION









REEL DIMENSION(FREE)






HRS DRAWING FOR REFERENCE

DETAIL OF TAPE FOR VACUUM PICKUP(5:1)





DRAWING NO.	EDC3-156320-02
PART NO.	FX6A-30S-0.8SV2(93)
CODE NO.	CL576-0322-7-93

△ 2/2