


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	3	RE-F-09671	K.N	H.Y	04.04.08						. .
					. .						. .
					. .						. .







RECOMMENDED LAND PATTERN DIMENSION OF P.C.B. (MOUNTING SIDE)



DIMENSION TABLE OF CONNECTOR AND P.C.B. LAND PATTERN.

PART No.	CODE No.	5	6	A	B	C	D	E
FX8C- 60P-SV6(92)	CL578-0601-3-92	60	×	24.60	23.00	20.70	17.40	22.20
FX8C- 80P-SV6(92)	CL578-0603-9-92	80	×	30.60	29.00	26.70	23.40	28.20
FX8C-100P-SV6(92)	CL578-0605-4-92	100	–	36.60	35.00	32.70	29.40	34.20
FX8C-120P-SV6(92)	CL578-0606-7-92	120	×	42.60	41.00	38.70	35.40	40.20
FX8C-140P-SV6(92)	CL578-0607-0-92	140	–	48.60	47.00	44.70	41.40	46.20

NOTE 1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
2. EMBOSSED CARRIER TAPE PACKAGING SHALL BE APPLIED FOR THIS PRODUCT.
SEE NEXT PAGE FOR DETAILS.
3. FOR MODIFICATION,ETC.,PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
4. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
5 NUMBER OF CONTACTS.
6 EXISTENCE
×:PRODUCED, – :NO PRODUCED

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
1,3	PPS	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min LEAD AREA:TIN-PLATING 1μm min UNDER PLATING:NICKEL 1μm min

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	S.SUZUKI	K.NAKAMURA	H.OKAWA	Y.YOSHIMURA	
	03.02.04	03.02.14	03.02.14	03.02.15	. .

SCALE	DRAWING NO.	PART NO.
FREE	EDC3-151090-22	FX8C-**P-SV6(92)
UNITS: mm	HRS HIROSE ELECTRIC CO., LTD	CODE NO. CL578 1/2


TO
PCK

HRS DRAWING FOR REFERENCE

Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .

UNREELING DIRECTION



FOR REFERENCE


REEL DIMENSION



△1 DIMENSION TABLE OF EMBOSSED CARRIER TAPE AND REEL.

PART No.	CODE No.	2	3	A	B	C	D	E	F
FX8C- 60P-SV6(92)	CL578-0601-3-92	60	×	20	25	20.2	40.4	44	44.4
FX8C- 80P-SV6(92)	CL578-0603-9-92	80	×	26	31	20.2	40.4	44	44.4
FX8C-100P-SV6(92)	CL578-0605-4-92	100	–	32	37	26.2	52.4	56	56.4
FX8C-120P-SV6(92)	CL578-0606-7-92	120	×	38	43	26.2	52.4	56	56.4
FX8C-140P-SV6(92)	CL578-0607-0-92	140	–	44	49	34.2	68.4	72	72.4

NOTE 1 1 RELL : 500 CONNECTORS
2 NUMBER OF CONTACTS
3 EXISTENCE
×:PRODUCED, –:NO PRODUCED



NO.	MATERIAL	FINISH, REMARKS
2	POLYESTER	(TOP COVER TAPE)
1	PS △1	(EMBOSSED CARRIER TAPE)

NO.	MATERIAL	FINISH, REMARKS
3		(CONNECTOR)

TO
PCK

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	S.SUZUKI	K.NAKAMURA	H.OKAWA	Y.YOSHIMURA	
	03.02.04	03.02.14	03.02.14	03.02.15	. .

SCALE	DRAWING NO.	PART NO.
FREE	EDC3-151090-22	FX8C-**P-SV6(92)
UNITS mm	HIROSE ELECTRIC CO., LTD	CODE NO. CL578 / 2