



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


HRS DRAWING FOR REFERENCE














Notes
1. Lead CO-PLANARITY shall be 0.1mm max.
2. For modification, etc., preventive hole for sink mark may be added according to circumstances.
3. The dimensions in parentheses are for reference.

NO.	MATERIAL	FINISH . REMARKS
1, 3	PPS	Light brown (UL94V-0)
2	PHOSPHOR BRONZE	Contact area : Gold 0.1μm min. Lead area : Tin-plating 1μm min. Under plating : Nickel 1μm min.

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△1	1	DIS-F-00006417	KS. NAKAJIMA	HT. YAMAGUCHI	20200803

HIROSE ELECTRIC CO., LTD.

APPROVED	HS. OKAWA	20051121
CHECKED	HS. OZAWA	20051121
DESIGNED	KY. NAKAMURA	20051118
DRAWN	KY. NAKAMURA	20051118


DRAWING NO.	EDC-150872-71-25
PART NO.	FX8C-80P-SV6(71)
CODE NO.	CL578-0603-9-71


△1 Added precaution


【Precaution】

When a board with multiple connectors mounted is mated, the connector may be damaged or deformed.
Please divide one side of the board so only one connector is mated per board.


OK








NG





HRS DRAWING FOR REFERENCE

Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS	DRAWING NO.	EDC-150872-71-25
	PART NO.	FX8C-80P-SV6(71)
	CODE NO.	CL578-0603-9-71