




Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




















HRS DRAWING FOR REFERENCE

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	STAINLESS STEEL	GOLD PLATING	6	STAINLESS STEEL	Spring washer
2	PTFE		5	STEEL	0-80UNF-2A Screw
1	STAINLESS STEEL	PASSIVATE	4	BERYLLIUM COPPER	GOLD PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	4	1	DIS-D-00016754	YJ. HAGA	TS. KANEKO	20230904

HIROSE ELECTRIC CO., LTD.

APPROVED	KY. SHIMIZU	20160830	DRAWING NO. EDC-366760-11-01
CHECKED	TO. KATAYAMA	20160830	PART NO. HK-R-SR2-1(11)
DESIGNED	TP. MATSUMOTO	20160829	
DRAWN	TP. MATSUMOTO	20160829	CODE NO. CL0338-0003-0-11

4 1/1

1> When mating the connector, please hold milling area of 5.8±0.2 with spanner not to place stress on PCB by the torque.
2> 0-80UNF-2B Screw tightening torque is 0.09N・m. Please tighten the screws evenly when mounting the connectors to ensure stable electrical contact.
3> Please use attached screw and washer for PCB mounting. Attached screw and washer apply PCB thickness T=2.4 to 4.25mm.
4> ▨ Indicates the area that solder mask is prohibited.
△4 5. This Product is a solderless mounted connector for prototype evaluation of high speed transmission boards. It is not recommended for use in actual commercial equipment.