

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


Unified screw thread type




A(10 : 1)




NOTES
1. WHEN THE MATING CONNECTOR, PLEASE HOLD MILLING AREA OF 5.8±0.2 WITH A WRENCH.
2. 0-80UNF-2B SCREW TIGHTENING TORQUE IS 0.09N・m.
   PLEASE TIGHTEN THE SCREWS EVENLY WHEN MOUNTING THE CONNECTORS TO ENSURE STABLE ELECTRICAL CONTACT.
3. PLEASE USE A PCB MOUNTING SCREW OF THE LENGTH OF L(mm).
   THE LENGTH OF L(mm) IS PCB THICKNESS t1(mm) + SPRING WASHER THICKNESS t2(mm) + 2(mm).
   PLEASE USE A SCREW WITH SPRING WASHER.
△3 4. THIS PRODUCT IS A SOLDERLESS MOUNTED CONNECTOR FOR PROTOTYPE EVALUATION OF HIGH SPEED TRANSMISSION BOARDS.
   IT IS NOT RECOMMENDED FOR USE IN ACTUAL COMMERCIAL EQUIPMET.



MOUNTING DRAWING(2 : 1)



RECOMMENDED PC BOARD PATTERN DRAWING(4 : 1)



REGIST FOR SIGNAL PAD AND GROUND PAD IS PROHIBITED.

HRS DRAWING FOR REFERENCE

RoHS COMPLIANT

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	PTFE				
1	BRASS	GOLD PLATING	3	BERYLLIUM COPPER	GOLD PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△3	1	DIS-D-00016695	NM. TORIUMI	TS. KANEKO	20230824

HIROSE ELECTRIC CO., LTD.

APPROVED	MH. YAMANE	20120210	DRAWING NO. EDC-339103-00-00
CHECKED	MH. TSUCHIDA	20120210	PART NO. HRM(G)-300-468B-1
DESIGNED	RO. YOKOYAMA	20120210	CODE NO. CL0323-0924-8-00 △3 1/1
DRAWN	RO. YOKOYAMA	20120210	