





- Notes
- ① The recommended clamp torque of REF. No. ① to be 2 to 2.5 N·m.
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent
REF. No. ① from loosening.
 - ② The recommended clamp torque of REF. No. ④ to be 0.65 to 0.7 N·m.
 - ③ Sealing and airtightness and oil resisting shall be tested
under mated condition with an applicable connector.

2	POLYPHENYLENE SULFIDE	(BLACK)	UL94V-0	4	STAINLESS STEEL	M3×0.5×8		
1	BRASS	NICKEL PLATING		3	ACRYLONITRILE BUTADIENE RUBBER	(GRAY)		
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS		
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED	HY. KOBAYASHI	18.02.26	DRAWING NO.	EDC-110599-32-00		
		CHECKED	HY. KOBAYASHI	18.02.26	PART NO.	JR13WCC-9(32)		
		DESIGNED	TH. KAMEYA	18.02.23	CODE NO.	CL114-2050-0-32		
		DRAWN	MK. INOUE	18.02.13			1/1	